



A British Lubricants Company

SAFETY DATA SHEET

CLP – Regulation (EC) No.2015/830

Page: 1
Revised Edition No. 6
Date: 01/10/2020
Supersedes: Edition 5

DRY MOLY COATING SPRAY

Part Number: BL-61001

1. IDENTIFICATION OF THE SUBSTANCE/ USE/ COMPANY DETAILS

Trade Name: Dry Moly Coating Spray
Company Identification: Brit-Lube Limited
Units 2&3 Mayfield Industrial Estate
Liverpool Road
Irlam
Manchester, M44 6GD
Tel: +44(0)161 777 9970
Fax: +44(0)161 777 9980
info@brit-lube.com
Type of product: Aerosol
Use: Lubricant/ Release Agent

2. HAZARDS IDENTIFICATION

Classification under CLP: H222; Extremely Flammable Aerosol
H229; Pressurised container may burst if heated

Label elements:

Signal word: Danger

Hazard Statements: H222; Extremely Flammable Aerosol
H229; Pressurised container may burst if heated

Pictograms: GHS02: Flame



Precautionary statements: P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C
P251: Do not pierce or burn, even after use
P210: Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. No smoking
P211: Do not spray on an open flame or other sources of ignition
P271: Use outdoors in in well ventilated area
P501: Dispose of contents/ container to local / national regulations

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients:

Substance Name	Contents	CAS No	Elnecs	PBT/WEL	CLP Classification
Hydrocarbon aerosol propellant	>50%	68476-85-7	270-704-2	Substance with community Exposure limit	Flam.Gas 1:220 Press Gas: H280 Flam Liq: H220 Eye Irrit.2: H319 STOT SE3; H336 Flam Liq:H226 Acute Tox4: H332 Acute Tox: 4: H312 Skin Irrit 2: H315
Acetone	20-30%	67-64-1	200-662-2		
Xylene	0.3 – 3.0%	1330-20-7	215-535-7		
Molybdenum Disulphide	3.0 – 10%	1317-32-5	215-263-9	Substance with community Exposure limit	

4. FIRST AID MEASURES

Inhalation	Use in a well ventilated area.
Skin Contact	Wash skin thoroughly with mild soap and water.
Eye Contact	Wash out eye with plenty of water. Obtain medical attention if soreness or redness persists.

5. FIRE FIGHTING MEASURES

Prevention	Do not expose to naked flames or fire. No smoking.
Extinguishing Media	Dry Chemical, Carbon dioxide
- Unsuitable extinguishing media	Do not use high pressure water
Surrounding Fires	Use water spray to cool containers
Specific Hazards	Under fire conditions, hazardous fumes will be present
Protection for Fire-Fighters	Do not enter fire area without Proper Protective Equipment, including respiratory equipment.
Special procedures	Exercise caution when entering any lubricant or chemical fire.

6. ACCIDENTAL RELEASE MEASURES

General Precautions	May be slippery if spilled. Remove from ignition sources. Do not breathe fumes or vapours from decomposition.
Personal Precautions	Avoid contact with skin and eyes. No Smoking. Clean up crews should wear proper Proper Protective Equipment.
Environmental Precautions	Prevent entry to sewers and public water ways. Notify authorities if product enters sewers or public waters
Clean up methods	Collect spill and put in appropriate container.

7. HANDLING AND STORAGE

GENERAL	Ensure there is adequate ventilation. Avoid all unnecessary exposure to naked flames or potential fire risks. No Smoking.
STORAGE	Store away from heat, sparks, open flames. Store in cool, dry well ventilated areas.
HANDLING	Ensure prompt removal from eyes, skin, clothing. Wash hands and other exposed areas with mild soap and water before you eat, drink or smoke, leave work. Keep away from food, drink. Keep out of reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION

Respiratory Protection	No special respiratory protection equipment is recommended under normal conditions of use, if used with adequate ventilation. If used in confined area wear suitable mask.
Hand Protection	Wear Barrier Cream, if repeated or prolonged contact wear protective clothes
Skin Protection	Protective gloves, nitrile gloves
Eye Protection	Wear safety glasses with side-shields
Ingestion	When using do not eat, drink or smoke

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Aerosol
Colour	Grey
Odour	Solvent
Evaporation Rate	Fast
Solubility in Water (vol/vol)	Material insoluble in water
Density	0.86
Flash Point	<100°C

10. STABILITY AND REACTIVITY

Hazardous decomposition products	Combustion will generate smoke, carbon monoxide, carbon dioxide
Hazardous reactions	Highly Flammable when sprayed
Hazardous properties	None under normal conditions. Highly Flammable whilst being sprayed.
Materials to avoid	Strong oxidizing agents, acids.
Conditions to avoid	Naked flames, fires, direct heat

11. TOXICOLOGICAL INFORMATION

Inhalation	Not expected to prevent a significant inhalation hazard under anticipated conditions of normal use. Inhalation of mists or vapours at elevated temperatures may cause respiratory irritation.
Dermal	Repeated or prolonged exposure may have a defatting effect or cause dermatitis.
Ocular	Redness, pain may occur.

12. ECOLOGICAL INFORMATION

On Product	Prevent entry to sewers and public water ways.
Ecological Effects	Not soluble in water, so only minimally bio-degradable

13. DISPOSAL CONSIDERATIONS

General	Dispose of in a safe manner in accordance with local/national regulations
Disposal method	In accordance with local/national regulations may be taken to waste disposal site.
Disposal of used packaging	Use a licensed waste disposal contractor.

14. TRANSPORT INFORMATION

General Information

Classification including:
UN Class: 1950, ADR Class: 2, RID Class: 2,
IMDG Class: 2, Un No. 1950, EmS:2-13, Labeling: 2.2
IATA Class: 2, UN No. 1950, Labeling: Extremely Flammable

15. REGULATORY INFORMATION

A chemical safety assessment has not been carried out for the substance or mixture by the supplier

16. OTHER INFORMATION

Product Use: For Industrial use only. Lubricant/ coating

Phrases used in S2,S3

H222; Extremely Flammable Aerosol
H229; Pressurised container may burst if heated
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C
P251: Do not pierce or burn, even after use
P210: Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition
P211: Do not spray on an open flame or other sources of ignition
P271: Use outdoors in well ventilated area
P501: Dispose of contents/ container to local / national regulations

The contents and format are in accordance with the following directives:

EU Commission regulation (EU) No 2015/830

EC Directive 94/1/EC adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of member States relating to aerosol dispensers

DISCLAIMER OF LIABILITY:

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user. The conditions of handling, storage, use or disposal of the product are beyond our control. For this and other reasons, we do not assume responsibility and expressly disclaim any liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. This MSDS was prepared solely for the product stated and should not be used for any other product.

END OF DOCUMENT.