

AUTHORISED DISTRIBUTOR



A British Lubricants Company

Trust Brit-Lube Specialist Lubricants
A Family owned International Brand!



Series
BT60/BT120/BT240



022-190186



KLT Co., Ltd.
型号(Model):
BT60 CMIIT ID: 2019DJ0846
BT120 CMIIT ID: 2019DJ0847
BT240 CMIIT ID: 2019DJ1090

IP65

Patent Nr: 10-2010757

New Generation, Bluetooth-Enabled Automatic Lubricator.



Pulsarlube BT

Features & Advantages

Convenient Lubrication Management

Conveniently control and monitor lubricators using the Pulsarlube mobile app
Various grease pouch capacities and lubricant types available

Enhanced User-Friendliness

Straightforward installation and operation
Easy to use app interface

Integrated DB Management

Keep track of operational status of all paired lubricators by using the integrated database

Safe Working Environment

Remotely monitor lubricator status in hazardous and inaccessible work areas via mobile app in close proximity

Outstanding Performance

- ▶ Bluetooth 4.1 enables connections up to 20m (66ft) away
- ▶ High output pressure enables remote installation up to 6m (20ft)
- ▶ Ingress Protection Rating : IP65


Typical Industries and Applications



- Hard to reach areas where maintenance access is not easy
- Hazardous locations where it is not safe to perform routine maintenance
- Where bearings are located in close proximity
- Where lubrication management is tedious and inconvenient

Overview

Product Specifications



Grease Pouch Capacity

60ml / 120ml / 240ml (pre-set)

Power Supply

DC 4.5V Battery Pack (replaceable)
Standard : Alkaline Battery
Optional : Lithium Battery

Operating Pressure

30 ~ 60bar (435~870psi)

Operating Temperature

Standard Alkaline Battery :
-15°C ~ 60°C (5°F ~ 140°F)
Optional Lithium Battery :
-40°C ~ 60°C (-40°F ~ 140°F)

Dispensing Periods

1 ~ 12 month

Single Point Remote Installation

Max. 6m (20ft) with Ø6 tube

Multi-Point Installation

Max. 3m (10ft) per point with Ø6 tube (Up to 8 lube points)

Dispensing Volume

0.34ml/stroke (@ 20°C/68°F)

Product Certifications & IP Code

CE / KC / FCC / SIG / NCC / RCM / SRRC / NBTC / ICASA / J-MIC / IP65

Bluetooth Range

5 ~ 20m depending on installation environment

Bluetooth Specifications

Bluetooth 4.1 (class 2)



A British Lubricants Company

1 Download

ANDROID



iOS



User Manual



Promo Video





Scan the QR codes with your smart phone or search for Pulsarlube BT in Google Play or App Store. User manuals are also available in the App under settings.

2 Sign In





Open the Pulsarlube BT App to sign in for a new account or enter your log-in credentials.

3 Pair



Log into "Registration" and select lubricators you wish to the account. Tap Register and log out.

4 Manage



Log into "General" to access status of registered lubricators, change lubricator settings and export data.

5 Upload



bt.pulsarlube.com

Lubricator data is easily accessible on the server website.



A British Lubricants Company